



THERMOCOUPLE CALIBRATION FURNACE - PTC

The PTC thermocouple calibration furnace is designed to provide a high stability portable heat source for the calibration of thermocouples using the comparison method.

STANDARD FEATURES

- | 1200°C maximum operating temperature
- | High stability heat source with temperature range 400 to 1150°C
- | Accepts thermocouples up to 7.5mm diameter
- | Thermocouple is inserted & compared to the PTC 12/20's displayed temperature
- | PID temperature control & separate temperature display to 1.0°C resolution
- | The special work tube design provides better temperature uniformity than is typical for a furnace of this size
- | The metallic work tube is earthed for operator safety when testing metal sheathed mineral insulated mineral thermocouples
- | Rapid heat up and stabilisation makes it ideal for use in the laboratory or on site
- | Portable & self contained

OPTIONS (*SPECIFY THESE AT TIME OF ORDER*)

- | Factory calibration certificate stating the error between the workspace temperature & the displayed value at 700°C, 900°C, & 1100°C
- | A UKAS traceable calibration certificate for customer defined setpoints is available
- | A UKAS calibrated thermocouple is available

THERMOCOUPLE CALIBRATION FURNACE - PTC

TECHNICAL DATA

PTC

Max temp (°C)	1200
Heat-up time to 1150°C (mins)	20
Temperature range (°C)	400 to 1150
Stability (±°C)	0.5 @ 1150°C
Heated length (mm)	150
Dimensions: Fixed tube inner diameter (mm)	20
Dimensions: External H x W x D (mm)	399 x 310 x 225
Max power (W)	1100
Thermocouple type	N
Weight (kg)	8.8

Please note

- Maximum continuous operating temperature is 50°C below maximum temperature

www.carbolite.com/ptc